WebSensor - remote barometer with Ethernet interface



code: T2514

Atmospheric pressure t-line Web sensor. Remote alarm.

Web Sensor with built-in atmospheric pressure sensor. Display reading and pressure output is user selectable in these units: hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2.

Processing and analysis of measured data:

- online in COMET Cloud
- COMET Database software
- integration into 3-party systems

With a newly purchased WebSensor with Ethernet communication, you receive 3 months of COMET Cloud. for free; a full year of operation in COMET Cloud. then requires 1 credit.

Technical data

ATMOSPHERIC PRESSURE SENSOR SENSOR	
Measuring range	600 to 1100 hPa
Accuracy	±1.3 hPa at 23 °C from 800 to 1100 hPa
Resolution	0.1 hPa
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +80 °C
Channels	internal atmospheric pressure sensor
Output	Ethernet
Measuring interval	2 s
Available pressure units	hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2
Communication protocol	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alarm protocols	E-mail, SNMP Trap, Syslog
Power	9-30 Vdc
Protection class	IP30
Dimensions	88,5 x 98 x 39,5 mm
Weight	approx. 150 g
Warranty	3 years