CO2 concentration and temperature transmitter with 4-20mA outputs, built-in sensors

code: T8148

CO2 - carbon dioxide level and temperature sensor.

CO2 concentration and temperature transmitter with two 4-20mA outputs is specially designed for use in exacting interiors in building energy management and HVAC systems. It designed for easy installation on ordinary KU68 wiring boxes for household switches and sockets.
Large dual line LCD is possible to switch off.
Computerized design ensures long term stability and fail indication. Transmitter is designed for use in non-aggressive environment.

Green LED shines - CO2 concentration 0 to 1000 ppm

Yellow LED shines - CO2 concentration 1001 to 1200 ppm

Red LED shines - CO2 concentration 1201 ppm and more

Technical data

TEMPERATURE SENSOR	
Measuring range	-10 to +50 °C
Accuracy	±0.5 °C
Resolution	0.1 °C
CO2 SENSOR	
Measuring range	0 to 2000 ppm
Accuracy	±(50ppm +2% from reading) at 25°C and 1013hPa
Resolution	1 ppm
GENERAL TECHNICAL DATA	
Operating temperature	-10 to +50 °C
Channels	internal temperature sensor a CO₂
Counted values	dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy
Output	4-20 mA
Available temperature units	degrees Celsius, degrees Fahrenheit
Configuration of output	user adjustable from PC; measured range + value

Power	9-30 Vdc
Protection class	IP20
Dimensions	88 x 106 x 33 mm
Weight	approx. 150 g
Warranty	3 years