IoT Wireless Temperature and Relative Humidity Datalogger with connector for other temperature probe, with built-in 2G modem

code: U3631M



GSM datalogger is designed to record temperature and humidity from built-in sensors and temperature from external probe. In case of exceeded set limits, SMS and JSON messages can be sent via GPRS data connection. Measured values can be sent to the internet storage COMET Cloud, which is a complete monitoring, alarm and analysis system.

It is also possible to set the regular sending of JSON messages to COMET Database, the sending interval is adjustable. Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper.
The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

GSM recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard.**

With a newly purchased IoT wireless datalogger with a built-in modem, you receive 3 months of COMET Cloud for free; a full year of operation in COMET Cloud then requires 1 credit.

Technical data

TEMPERATURE SENSOR	
Measuring range	-20 to +60 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
TEMPERATURE SENSOR - external probe Pt1000	
Measuring range	-90 to +260 °C
Accuracy	±0.2 °C in the range -90 °C to +100 °C ±0.2 % of the measured value in the range +100 °C to +260 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	± 1.8 % RH
Resolution	0.1% RH
DEW POINT	
Measuring range	-90 to +60 °C
Accuracy	±1.5 °C at ambient temperature T <25 °C and RH >30 %
Resolution	0.1 °C
GSM MODEM PARAMETERS	
Quad-band	850/900/1800/1900MHz
Compliant to GSM	Phase2/2+
GPRS	GPRS mobile station class B

Class 4	2W @ 850/900MHz
Class 1	1W @ 1800/1900MHz
GENERAL TECHNICAL DATA	
Operating temperature	-20 to +60 °C
Channels	internal temperature and humidity sensor, 1x external temperature probe
Memory	500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode
Recording interval to the internal memory	adjustable from 1 second to 24 hours
Recording interval to the COMET Cloud	from 5 minutes
Interval for measuring and evaluating alarms	adjustable 1 s, 10 s, 1 min
Recording mode	noncyclic - data logging stops after filling the memory cyclic - after filling memory oldest data is overwritten by new
Real time clock	year, leap year, month, day, hour, minute, second
Power	rechargeable Li-Ion battery A8200, 3.6V/5200mAh
Protection class	IP67 electronics; IP30 sensors
Dimensions	61 x 93 x 53 mm, with antenna 120 x 93 x 53 mm
Weight (including batteries)	approx. 260 g
Warranty	3 years