IoT Wireless Temperature, Relative Humidity, CO2 and atmospheric pressure Datalogger with built-in 4G modem and Flat Rate SIM Card

code: U4440Gsim



IoT Wireless Datalogger kit with built-in 4G modem and Flat Rate SIM Card allows the instant connection to the COMET Cloud.
IoT Datalogger is designed to record temperature, humidity, atmospheric pressure and CO2 from built-in sensors. In case of exceeded set limits e-mail is sent from the COMET Cloud.

Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper.
The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

4G recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard.**

Optional CO_2 measuring range extension from the standard 0 to 5,000 ppm up to 0 to 10,000 ppm (available at extra cost):

- **Extended measuring range:** 0 to 10 000 ppm
- **Accuracy in extended range:** 100 ppm + 5% of the measured value at 25 °C and 1013 hPa

Technical data

TEMPERATURE SENSOR	
Measuring range	-20 to +60 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	± 1.8 % RH
Resolution	0.1% RH
DEW POINT	
Measuring range	-90 to +60 °C
Accuracy	±1.5 °C at ambient temperature T <25 °C and RH >30 %
Resolution	0.1 °C
CO2 SENSOR	
Measuring range	0 to 5000 ppm
Accuracy	±(50ppm +3% from reading) at 25°C and 1013hPa
Resolution	1 ppm
ATMOSPHERIC PRESSURE SENSOR SENSOR	
Measuring range	600 to 1100 hPa
Accuracy	±1.3 hPa at 23 °C
Resolution	0.1 hPa
4G MODEM PARAMETERS	
LTE Cat 1	LTE FDD/GSM/GPRS/EDGE

Supported network types	GSM/GPRS/EDGE 900/1800 MHz LTE FDD B1/B3/B5/B7/B8/B20
GENERAL TECHNICAL DATA	
Operating temperature	-20 to +60 °C
Channels	internal sensor for temperature, humidity, CO₂ and atmospheric pressure
Memory	500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode
Recording interval to the internal memory	adjustable from 1 second to 24 hours
Recording interval to the COMET Cloud	from 5 minutes
Interval for measuring and evaluating alarms	adjustable 1 s, 10 s, 1 min
Recording mode	noncyclic - data logging stops after filling the memory cyclic - after filling memory oldest data is overwritten by new
Real time clock	year, leap year, month, day, hour, minute, second
Power	rechargeable Li-Ion battery A8200, 3.6V/5200mAh
Protection class	IP20
Dimensions	61 x 93 x 53 mm, with antenna 120 x 93 x 53 mm
Weight (including batteries)	approx. 260 g
Warranty	3 years