

IoT Wireless Temperature Sensor for 4 external Pt1000 probes with CINCH connector, LoRaWAN network

code: W0941E



The W0941 sensor with LoRaWAN network output measures temperature from four external Pt1000 probes on the cable. LoRa devices are powered by a replaceable battery with a lifespan of up to 10 years (3 years standard). External power with optional accessories is also available.

Measured values are transmitted wirelessly at adjustable intervals (from 5 minutes to 24 hours) to the [COMET Cloud](#) storage, where they are accessible to users via computer or mobile device. The sensors offer remote configuration from the COMET Cloud and feature the capability to monitor up to two alarm thresholds, with any exceedance signaled by an alert sent to the user.

Key Features

- Wireless transmission of measured values and alarm states
- Battery-powered with low battery indicator (battery life up to 10 years) and external power option
- Remote device configuration via COMET Cloud
- Calibration certificate with declared metrological traceability of standards according to CSN EN ISO/IEC 17025
- Preconfigured Gateway available as an accessory at extra cost. For easy use, we offer [several types of preconfigured LoRaWAN gateways](#) that are fully prepared for communication with COMET Cloud and our sensors. This option simplifies the setup process and saves time for users

Technical data

| | |
|---|---|
| TEMPERATURE SENSOR - external probe Pt1000 | |
| Measuring range | -200 to +260 °C |
| Accuracy | ±0.2 °C in the range -90 to +100 °C; ±0.2 % from reading from +100 to +260 °C |
| Resolution | 0.1 °C |
| Response time t90 of temperature measurement (temperature step 20°C, air flow approximately 1m/s) | 10 minutes |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -20 to +60 °C |
| Channels | 4x external temperature probe, CINCH connector |
| Message transmission interval | adjustable 5-10-15-20-30 minutes, 1-2-3-4-6-8-12-24 hours |
| Operating frequency | Europe 863-870 MHz |
| Maximum transmission power | 25 mW (14 dBm) |
| Typical range of transmitter | 15 km in the field, 2 km in the city (sensor in building) |
| Antenna | internal, gain 2,15 dBi |
| Maximum receiver sensitivity | -136 dBm @BW=125 kHz, SF=12 |
| Power | Lithium battery 3.6 V, C size, capacity 8.5 Ah |
| Protection class | IP65 |

| | |
|------------------------------|--------------------------------------|
| Dimensions | 179 x 134 x 45 mm without connectors |
| Weight (including batteries) | 350g |
| Warranty | 3 years |